



Timber Refresh and Restore Product Information Booklet

1 Trio Wood Floor Cleaner



Trio Wood Floor Cleaner

High Alkaline Wood Floor Cleaning product. Designed to break down floor waxes contained in cleaning products such as “Pledge”.

Usage

Standard Floor Preparation

Mix 10:1 in a pump sprayer. Spray a heavy even coating on the floor and clean with a Polivac rotary machine (low speed) with either a maroon prep-pad or a dollar sand disc. Clean all edges with a doodlebug and detail corners by hand. Clean over with a walk behind floor scrubber with fresh hot water (use hot water from the tap – additional heating is not required).

Floor with Heavy Soiling or Wax Build Up

Mix 3:1 in a pump sprayer and apply a very heavy, even coating on the floor and allow a 10 minute dwell time. Clean with a Polivac using a maroon prep-pad. Clean over with a walk behind floor scrubber with fresh warm water. Repeat as necessary.

Wax build-up is usually evident by a varying sheen level. The floor will often be darker in the corners or edges of rooms where the build-up of wax is heaviest.

2 Timber Refresh Product



Timber Refresh Product

A polyurethane-acrylic hybrid polymer with a polyurethane backbone that adheres to raw timber and polyurethane as well as vinyl and laminate floors. Acts as a primer for Eukala Strato Extreme 2-pack Polyurethane coatings, used in the Timber restore service.

Timber refresh is a custom-made product, that is the only product of its' type and is made exclusively for Electrodry.

Longevity

The expected lifespan of a standard Timber Refresh service is 2 – 4 years, after which the client may choose to have the floors “refreshed again”.

Curing Times

- Ready to walk on and gently replace the furniture in one hour
- 95% cured in 24 hours
- 100% cured in 72 hours

Avoid wet-mopping the floor, do not replace rugs and minimise pets (especially large dogs) for 3 days from application.

Usage

Mix with **Crosslinker M** at a ratio of 50ml crosslinker to 1 litre of Timber Refresh

Timber Refresh: 1 litre per 60sqm per coat. 2 coats are required (mix 1 litre of product per 30 sqm of timber refresh service).

Timber Refresh + 2: 1 litre per 60sqm per coat. 3 - 4 coats are required (mix 1 litre of product per 20 sqm of Timber Refresh + 2 service).

Timber Restore: Use as required to build up a wear layer in worn areas (usually 3 to 6 coats) and apply in accordance with a timber refresh service for areas where the coating is intact and in reasonable condition.

3 Timber Refresh Product



Timber Refresh Product

A polyurethane-acrylic hybrid polymer with a polyurethane backbone that adheres to raw timber and polyurethane as well as vinyl and laminate floors. Acts as a primer for Eukala Strato Extreme 2-pack Polyurethane coatings, used in the Timber restore service.

Timber refresh is a custom-made product, that is the only product of its' type and is made exclusively for Electrodry.

Price

\$371.00 per 5 Litre Container

\$74.20 per litre

Timber Refresh Application Cost (with 25% wastage): \$3.01 per sqm. The cost of application with incidentals such as mopping pad, cloths, tape, booties and bag is \$3.50 per sqm

Timber Refresh + 2 Application Cost (with 25% wastage): \$4.67 per sqm Application with incidentals such as mopping pads, cloths, tape, booties and bag is \$5.30 per sqm.

Additional product usage must be allowed for a Timber Refresh + 2 service with a warm floor or when colours are added to minimise sun fading.

Application

Additional product usage must be allowed for a **Timber Refresh +2** service with a warm floor or when colours are added to minimise sun fading.

4 Strato Extreme High-Density Polyurethane Coating



Strato Extreme High-Density Polyurethane Coating

German-made high-density, waterborne 2-pack polyurethane coating. High performing floor coating with excellent scratch resistance.

Applied as the final coating for Timber Restore Service. Excellent bonding performance to Timber Refresh product when applied within 3 hours from the final Timber Refresh coating.

Longevity

The expected lifespan of a Timber Restore service with the Strato Extreme coating is 5 – 10 years.

Curing time

- Usually ready to walk on and gently replace the furniture in 2 – 4 hours, but up to 12 hours. Temperature, airflow and humidity will affect drying time
- 97% cured in 3 days hours
- 100% cured in 7 hours

Avoid wet-mopping for 7 days from application. Do not replace rugs for 7 days from application.

Usage

Mix with the **Crosslinker** supplied at a ratio of 100ml of **Crosslinker** to 1Litre of **Strato Extreme**. Apply at a ratio of 1 litre per 10 sqm.

Price

- \$239 per 5 litre container (with 500ml crosslinker)
- \$43.45 per litre
- \$5.21 per square metre (allowing for 20% wastage)

The costs of application including freight, rollers, brushes and tape is \$5.50 to \$6 per square metre.

Application

Apply with a 10 – 12 mm nap roller. Cut into the edges with a paintbrush. Always maintain a wet edge during application. Working over a tacky coating will result in a dull or orange peel finish.