

Electrodry Tile & Grout Clear Penetrating Sealer Process & Pricing



Electrodry Professional Services



The Electrodry Grout Sealing Process

Water
Based

Safe to use
Environmentally
friendly
Non-flammable
Often lower cost



Stone Sealer Pro

Commercial and domestic stone

Do not dilute

Performance

- Premium protection against staining caused by foods, beverages, coffee, wine, fats and oils.
- Excellent for outdoor projects. Well suited to very porous stone.
- UV stable, fully breathable, no appearance change.

Surface Compatibility

- Ideal for grout line, marble, limestone, travertine, sandstone, bluestone, slate, terracotta and concrete.

Safety

- Non hazardous. Non flammable..

The Electrodry Grout Sealing Process

Solvent
Based

Better penetration in
dense substrates.
Better performance
in some applications.



Solv Sealer Pro

Internal Floors, Counters, Features

Do not dilute

Performance

- Premium protection against staining caused by foods, beverages, coffee, wine, fats and oils.
- Maximum penetration ability. Excellent for dense substrate.
- UV stable, fully breathable, no appearance change.

Surface Compatibility

- Ideal for granite, marble, limestone, travertine.
- Ideal for polished porcelain

Only for treating whole stone tiles and grout

The Electrodry Grout Sealing Process

1. Thoroughly clean and dry the tiled area
2. Fill your grout wand with Stone Sealer pro.
3. Wheel the wand along the grout line in straight rows along the grout from wall to all
4. Allow 5-10 minutes, and wipe off excess from the tiles
5. Allow 10 minutes before next coat
6. **Apply a second coat**
7. Then repeat steps 2 - 4



Pricing

\$12-\$14 Per square meter

The Electrodry Grout Sealing Process

1. When a lot of sealer has landed on the tiles, possibly clean with Pro Neutro and a white nylon pad under the Polivac.
2. The grout wands come with 2 wheels of different sizes to match different size grout lines
 - These can be purchased as just the wheels.



Pricing

\$12-\$14 Per square meter

The Electrodry Grout Sealing Sample board

1. Shortly you will be able to order grout sealing sample boards similar to the image on the right.
2. Half of the grout lines will be sealed and half not sealed.
3. You can show your client what happens with sealer by placing water on the sealed line. It will bead compared to soaking in to the unsealed grout



The Electrodry Stone Penetrating Sealing Process

1. Thoroughly clean and dry the tiles
2. Saturate the up to 6sqm with sealer using a roller
3. Allow 5 minutes, squeegee off the excess to the next working area and wipe off excess from the tiles just treated
4. Allow 10 minutes before next coat
5. **Apply a second coat**
6. Repeat steps 2-4
7. Clean with Pro Neutro and a white nylon pad under the Polivac.



The Electrodry Stone Sealing Process

- Different stones require different sealers
- Solv Sealer Pro is ideal for granite, marble, limestone, travertine and polished porcelain
- Stone Sealer Pro is ideal for marble, limestone, travertine, sandstone, bluestone, slate, terracotta and concrete.

Pricing

Starts at \$20 Per square meter

Due to every stone tile being different, we ask that you be committed and provide a genuine and fair quote

The Electrodry Topical Stone Sealing

- Some of you may have done topical sealing which is a layer that goes over the top of stone tiles and grout lines.
- This service will not be covered here. If your managers feel you are ready for this, we will train you and explain the process then



Thank you!

